



**HEIM DATaRec® D20fe/D120f/D200f  
 storage media cartridges**

The media is built into cartridges, which can be interchangeably used in the D20fe, D120f, D200f and GSR series. All cartridges are identically used to allow data acquisition with flight certified equipment and analysis with laboratory systems.

**CSxxx solid state drive**

Media	Flash based solid state storage
Capacity	up to 128 Gbytes
Maximum bit rate	240 Mbit/s
Bit error rate	better than 10 <sup>-14</sup>
Vibration	10 g, MIL-STD-810E, category 4, 5 and 6
Acceleration	20 g, in all directions (continuous)
Shock	20 g MIL-STD-810E
Temperature	-30°C – +65°C, operating
Storage temp.	-40°C – +70°C, (long term)
Humidity	0 – 95% relative, non-condensing
Altitude	no limit

**CSLxxx hard disk drive**

Media	Flash based solid state storage (MLC-type)
Capacity	up to 128 Gbytes
Maximum bit rate	240 Mbit/s
Bit error rate	better than 10 <sup>-14</sup>
Vibration	5 g, MIL-STD-810E, category 4, 5 and 6

Acceleration	10 g, in all directions (continuous)
Shock	15 g, MIL-STD-810E
Temperature	-30°C <sup>1)</sup> – +45°C, operating
Storage temp.	-40°C – +60°C, (long term)
Humidity	20 – 90% relative, non-condensing
Altitude	no limit

**IRIG 106 chapter 10 option**

The IRIG 106 chapter 10 option is marked with a "1". With this option the media cartridges have the following added functionality.

Download port	IEEE 1394b
Directory structure	STANAG 4575

This option is available for CSxxx, CSLxxx (no declassify) cartridges.

**Notes**

<sup>1)</sup> special start-up procedure required

**ZODIAC Data Systems GmbH**

Friedrich-Ebert-Strasse / TechnologiePark – D-51429 Bergisch Gladbach  
 Tel.: +49 2204 84 41 00 – Fax: +49 2204 84 41 99  
 info.heim@zodiacaerospace.com – http://www.zodiac-data-systems.com

©ZODIAC Data Systems GmbH

